



# RMS-3 RACKMOUNT WINGS

## ASSEMBLY GUIDE

For fitting non-rackmount units into 19" equipment racks, this 16 gauge steel kit consists of a pair of 3u rackmounting wings with a central vertical slot, and rear horizontal slot. These allow two 'L' shaped clamp bars to grip the unit from above and from the rear.

Hold one clamp bar against the inside of the vertical slot (a) in the left wing, and insert the bolt from outside the wing into the nut at the end of the bar. Do the same with the other bar at the rear horizontal slot (b), then attach the right wing (c) to the other ends of the bars in the same way. Fit into your 19" rack, and place the unit to be racked on the wings.



Lower the vertical bar onto the top of the unit (you may want to attach some sticky-backed foam strip to the underside of the bar to avoid marking) and tighten the bolts. Slide the horizontal bar up to the back edge of the unit and tighten the bolts. Large items like cassette decks and CD players will sit on the wings - smaller units like half-racks, DAT players etc. sit on the *optional* steel shelf. Fix to the wings by inserting the 4 plastic rivets supplied through the shelf into the holes in the wings.

*Download the MTR e-book for PC's from our website. We welcome owner-user feedback on our products*

**MTR Ltd. FORD HOUSE, 58 CROSS ROAD, BUSHEY, HERTS, WD19 4DQ UK**  
Tel :+44 (0)1923 - 234050. Fax: -255746 e-mail: [mtrltd@aol.com](mailto:mtrltd@aol.com) [www.mtraudio.com](http://www.mtraudio.com)